

Everlast

Tankless Hot Water Heaters

**5.3 Gallons per minute continuous.
Never run out of hot water again!
Save up to 70% on your water heating costs!**



92% Efficient

Features:

- Control the temperature within 89.6 F -176 F.
- High efficient and energy saving combustion system
- Intelligent alarm system
- The low-noise high-speed blower fan is designed to exhaust to the outside and bring in outdoor air for combustion
- Low water pressure startup ≥ 0.075 gal/min
- Automatically shuts off gas supply when no water is detected
- Draft switch protection in case of a blocked flue
- Overheating protection automatically cuts off when water temperature exceeds 194 degrees F
- Ignition delay device
- Electronic Ignition – No pilot light

Specifications:

- Natural Gas
- Thermal efficiency $\geq 92\%$
- Electronic pulse ignition
- Forced exhaust system 5" metal vent for 1-2 units, 8" for 3 units, 10" for 4-5 units.
- Electric motor 110V/60Hz 30 W - Battery operated.
- Exhaust vent pipe length: up to 41' with no more than 2 - 90° elbows
- Applicable water pressure: 2 psi – 72 psi
- Gas, Cold and Hot water pipe: 1/2"
- 10 "D x 14"W x 23"L

Everlast

Phone: 801-471-5444 or 801-885-8775

Pacific Northwest Customers call Porter Block, Inc. 406-862-1496